

## 1. IDENTIFICATION OF THE SUBSTANCE PREPARATION AND COMPANY UNDERTAKING

## 1.1 PRODUCT IDENTIFIER

Product name: Extra High Yield Black Toner Cartridge for Lexmark X792

Part number: LEXX792B

#### 1.2 IDENTIFIED USES AND USES ADVISED AGAINST

For use in: Laser Printers

1.3 **SUPPLIER DETAILS** 

Supplier: Clover Imaging Group

4200 Columbus Street Ottawa, IL 61350 United States

Phone number: 815-431-8100

Fax: 815-461-8583

Contact Hours: 08:00AM-05:00PM CST

## 1.4 EMERGENCY TELEPHONE NUMBERS

Supplier: 815-431-8100

# 2. HAZARDS IDENTIFICATION

#### 2.1 INFORMATION and CLASSIFICATION

Overview: OSHA Hazard Classification: This product is an article which contains a mixture/preparation in powder

form. Safety information is givien for exposure to the article as sold and used by the customer. Intended use of the product is not expected to result in exposure to the mixture/preparation based on the packaging and method of dispensing. While this material is not considered hazardous by the OSHA hazard Communication Standard (29 CFR 1910.1200) this SDS contains valuable information for the safe handling and proper use of the product. This SDS should be retained and made available to employees and others users of this product. HAZARD STATEMENTS: May cause combustible dust concentrations in air. PRECAUTIONARY STATEMENTS: Prevent dust cloud. Sweep up or vacuum with electrically protected vacuum cleaner and collect in suitable container for disposal. Use non-sparking

tools and equipment. Keep away from sources of ignition - No smoking.

# 2.2 **LABEL ELEMENTS**

Applicable Pictograms:

NO PICTOGRAM

Danger Indications: No hazard expected under normal conditions of use.

Risk Phrases: N/A

Safety Phrases: Signal word: Warning

2.3 OTHER HAZARDS

PBT or vPvB: N/A

Product: Extra High Yield Black Toner Revision date: 08/08/2017 Page: 1/9

<sup>\*</sup> This document provides safety-related information about ink/toner, in various forms, for use in copiers/printers etc.



## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS number	Weight %	OSHA	ACGIH	Other
			PEL	TLV	
Polymer	292629-36-8	80-90			
Polyethylene Wax	9002-88-4	5-15			
Carbon Black	1333-86-4	5-10	TWA: 3.5	TWA: 3	Classification (Reg. 1272/2008):
			mg/m3	mg/m3	Carc 2 (inhalation). Hazard
					Statements H351.

The Full Text for all R-Phrases are Displayed in Section 16

#### **COMPOSITION COMMENTS**

The Data Shown is in accordance with the latest Directives.

This section provides composition information for the specified substance/mixture.

#### 4. FIRST-AID MEASURES

#### 4.1 FIRST AID MEASURES

#### 4.1.1 FIRST AID INSTRUCTIONS BY RELEVANT ROUTES OF EXPOSURE

Inhalation: Move to fresh air.

Eye contact: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes.

Skin contact: Wash skin with soap and water.

Ingestion: Rinse mouth with water and afterwards drink plenty of water or milk.

#### 4.1.2 ADDITIONAL FIRST AID INFORMATION

Additional first aid information: N/A

Immediate Medical Attention Required: Treat symptomatically.

# 4.2 **SYMPTOMS AND EFFECTS**

Acute Symptoms from Exposure: No known effect.

Delayed Symptoms from Exposure: No known effect.

#### 4.3 IMMEDIATE SPECIAL TREATMENT OR EQUIPMENT REQUIRED

Protection to first-aiders: No special equipment required. Notes to physician: Treat symptomatically.

Product: Extra High Yield Black Toner Revision date: 08/08/2017 Page: 2/9



# 5. FIRE-FIGHTING MEASURES

## 5.1 EXTINGUISHING MEDIA

Extinguishing Media Not to be Used: Do not use a solid water stream as it may scatter and spread fire.

5.2 **SPECIAL HAZARD** 

Unusual Fire/Explosion Hazards: Fine dust dispersed in air, in sufficient concentrations, and in the presence of an

ignition source is a potential dust explosion hazard. Hazardous decomposition products due to incomplete combustion, Carbon oxides, Nitrogen oxides (NOx).

Extinguishing Media Not to be Used: N/A

#### 5.3 ADVICE FOR FIRE FIGHTERS

Avoid inhalation of smoke. Wear protective clothing and wear self-contained breathing apparatus

## 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

## 6.1.1 PRECAUTIONS FOR NON-EMERGENCY PERSONNEL

Avoid breathing dust.

## 6.1.2 ADDITIONAL FIRST AID INFORMATION

N/A

## 6.1.3 PERSONAL PROTECTION

Wear personal protective equipment as described in Section 8.

# 6.2 **ENVIRONMENTAL PRECAUTIONS**

Regulatory Information: Keep product out of sewers and watercourses.

## 6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANUP

Spill or Leak Cleanup Procedures: Methods for containment: Prevent dust cloud. Methods for cleaning up: Use a vacuum

cleaner to remove excess, then wash with COLD water. Hot water fuses the toner making it

difficult to remove.

Product: Extra High Yield Black Toner Cartridge for Lexmark X792 Revision date: 08/08/2017 Page: 3/9



## 7. HANDLING AND STORAGE

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

Recommendations for Handling: No special precautions when used as intended. Keep containers closed. If toner, avoid

creating dust. Keep away from ignition sources.

Advice on General Hygiene: Never eat, drink or smoke in work areas. Practice good personal hygiene after using this

material, especially before eating, drinking, smoking, using the restroom, or applying

cosmetics.

#### 7.2 **CONDITIONS FOR SAFE STORAGE**

Avoid high temperatures, >100°F/32°C

## 7.3 **SPECIFIC END USES**

Printing devices

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 **CONTROL PARAMETERS**

The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release in order to maintain airborne concentrations of the product below OSHA PELs (See Section 3).

Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

## 8.2 **EXPOSURE CONTROLS**

#### Respiratory protection:

IMPROPER USE OF RESPIRATORS IS DANGEROUS. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134 and 1910.137) and, if necessary, wear a NIOSH approved respirator. Select respirator based on its suitability to provide adequate worker protection for given work conditions, levels of airborne contamination, and sufficient levels of oxygen.

# **Eye/Face Protection:**

Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

#### Hand/Skin Protection:

For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. WARNING! Air purifying respirators do not protect worker in oxygen deficient atmospheres.

#### **Additional Protection:**

N/A

#### **Protective Clothing and Equipment:**

Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear splash-proof chemical goggles and face shield when working with liquid, unless full face piece respiratory protection is worn.

## **Safety Stations:**

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

## **Contaminated Equipment:**

Separate contaminated work clothes from street clothes. Launder before reuse. Remove material from your shoes and clean personal protective equipment. Never take home contaminated clothing.

#### Comments:

Never eat, drink or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the restroom, or applying cosmetics.

Product: Extra High Yield Black Toner Revision date: 08/08/2017 Page: 4/9



## 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 **DETAIL INFORMATION**

Physical state: APPEARANCE: Black powder.

Color: Black
Odor: Faint
Odor threshold: N/A

Boiling point: Not applicable
Melting point: Not determined
Flash point: Not applicable

Explosion limits: See "Other Information" in this section.

Relative density: N/A

Auto-ignition temperature: Not applicable

## 9.2 OTHER INFORMATION

Method: ASTM E 1226 Standard Test Method for Explosibility of Dust Clouds. Maximum rate of explosion pressure rise (KSt): 282 - 304 m\*bars/sec. Maximum explosion pressure (Pmax): 7.9 - 9.0 bar. Minimum ignition energy: <3 millijoules.

## 10. CHEMICAL STABILITY AND REACTIVITY

## 10.1 Reactivity:

Reactivity Hazards: None

Data on Mixture Substances: None

10.2 **Chemical Stability:** The product is stable. Under normal conditions of storage and use, hazardous

polymerization will not occur.

10.3 **Hazardous Polymerization:** Stable under conditions of normal use.

10.4 **Conditions to Avoid:** Keep away from heat, flame, sparks and other ignition sources.

10.5 **Incompatible Materials:** Strong oxidizing materials

10.6 Hazardous Decomposition: Will not occur.

Product: Extra High Yield Black Toner Cartridge for Lexmark X792 Revision date: 08/08/2017 Page: 5/9



## 11. INFORMATION ON TOXICOLOGICAL EFFECT

Mixtures: N/A

Oral LD50: > 5g/kg (rat). Dermal LD50: > 5g/kg (rabbit). LC50 Inhalation: > 5ml/L (rat, 4hr). **Acute Toxicity:** 

Skin Corrosion/Irritation: No skin irritation. **Serious Eye Damage:** No eye irritation. Inhalation: No data available.

Sensitization: No sensitization responses were observed.

**Mutagenicity:** Not mutagenic in AMES Test

Carcinogenicity: Carbon Black: IARC 2B. The IARC (International Agency for Research on Cancer) has listed carbon

> black as "possibly carcinogenic to humans." However, we have concluded that the pressence of carbon black in this mixture does not present a health hazard. The IARC classification is based on studies evaluating pure "free" carbon black. In contrast, toner is a formuation composed of specially prepared polymer and a small amount of carbon black (or other pigment). In the process of making toner, the small amount of carbon black becomes encapsulated within a matrix.

Extensive testings of toner, including a chronic bioassay (test for potential carcinogenicity). Exposure to toner did not produce evidence of cancer in exposed animals. The results were

submitted to regulatory agencies and published extensively.

**Reproductive Toxicity:** No information available.

STOT - Single Exposure: N/A **STOT - Multiple Exposure:** N/A

Ingestion: No data available.

Hazard Class Information: N/A Mixture on Market Data: N/A Symptoms: N/A Delayed/Immediate Effects: N/A Test Data on Mixture: N/A **Not Meeting Classification:** N/A Routes of Exposure: N/A Interactive Effects: N/A **Absence of Specific Data:** N/A

Mixture vs Substance Data: N/A

## 12. ECOLOGICAL INFORMATION

On data available, substance is not harmful to aquatic life. Carbon Black - Toxicity to daphnia 12.1 Eco toxicity:

and other aquatic invertebrates: EC50> 5600 mg/L 24h.

12.2 Degradability: No information available.

12.3 Bioaccumulation Potential: Bioaccumulation is unlikely.

12.4 Mobility in Soil: Insoluble in water.

12.5 PBT & vPvB Assessment: N/A

12.6 Other Adverse Effects: Presents little to no hazard to the environment.

Product: Extra High Yield Black Toner Revision date: 08/08/2017 Page: 6/9



## 13. DISPOSAL CONSIDERATIONS

#### **Disposal Information:**

Dispose of product in accordance with local authority regulations.

Empty container retains product residue.

## **Physical/Chemical Properties that affect Treatment:**

Symbol: This product is not classified as dangerous

Risk Phrases: This product is not classified according to the federal, state and local environmental regulations.

#### **Waste Treatment Information:**

If toner, do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

# **Personal Protection Required:**

N/A

## 14. TRANSPORT INFORMATION

14.1 **ID Number:** Not regulated.

14.2 **Shipping Name:** Not regulated.

14.3 Hazard Class: Not regulated.

14.4 **Packing Group:** Not regulated.

14.5 Environmental Hazards: N/A

14.6 User Precautions: N/A

14.7 Bulk Transport: N/A

# 15. REGULATORY INFORMATION

15.1 **Regulatory Information:** OSHA Regulatory Status: This material is not considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200). Canada: This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR), and the

SDS contains all the information required by the HPR.

EPA Regulatory Information: Clean Water Act: This product is not regulated as a pollutant puruant to the Clean Water

Act (40 CFR 122.21 and 40 CFR 122.42). Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61): This product is not regulated as a hazardous air pollutant (HAPS) under section 112 of the Clean Air Act Amendments of 1990.

**CERCLA Reportable Quantity:** This material, as supplied, does not contain any substances regulated as hazardous

substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state

level pertaining to releases of this material.

# 15.2 Superfund Information:

**Hazard Categories:** 

Immediate: N/A

Delayed: N/A

Fire: N/A

Pressure: N/A
Reactivity: N/A

Section 302 - Extremely Hazardous: N/A

Product: Extra High Yield Black Toner Cartridge for Lexmark X792 Revision date: 08/08/2017 Page: 7/9



Section 311 - Hazardous: N/A

15.3 **State Regulations:** California Proposition 65: Carbon black is regulated under California Proposition 65 only if

in the form of "airborne, unbound particles of respirable size". Toner products do not contain carbon black in the form of "airborne, unbound particles of respirable size."

Therefore, the requirements of Proposition 65 do not apply to this product.

15.4 Other Regulatory Information: N/A

16. OTHER INFORMATION

**General Comments:** This information is based on our current knowledge. It should not therefore be construed as

guaranteeing specific properties of the products as described or their suitability for a particular

application

**Creation Date of this SDS:** 01/25/2021

Product: Extra High Yield Black Toner Cartridge for Lexmark X792 Revision date: 08/08/2017 Page: 8/9



# Key to Abbreviations and Acronyms used in this sheet:

ACGIH = American Conference of Governmental Industrial	NIOSH = National Institute for Occupational Safety and Health		
Hygienists			
CERCLA = Comprehensive Environmental Response Compensation	OSHA = Occupational Health and Safety Administration		
and Liability Act			
CLP = Classification, Labeling, and Packaging	PEL = Permissible Exposure Limit		
DSD = Dangerous Substances Directive	SCBA = Self Contained Breathing Apparatus		
EPA = Environmental Protection Agency	STOT = Specific Target Organ Toxicity		
GHS = Globally Harmonized System	TLV = Threshold Limit Value		
N/A = Not Applicable	UK = United Kingdom		
NFPA = National Fire Protection Association	UN = United Nations		

_		-	
D	0	٠	

# DISCLAIMER

All trademarks and models referenced are property of their respective holders and are used for identification purposes only. These products are not sponsored by, affiliated with, manufactured by or distributed by the named manufacturers.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Product: Extra High Yield Black Toner Cartridge for Lexmark X792 Revision date: 08/08/2017 Page: 9/9